

SCHWEGO[®] eco foam 6326

Defoamer and deaerator for water-based coating systems, free of VOC

Chemical base: Emulsion of oils and hydrophobic components

Properties: **SCHWEGO[®] eco foam 6326** is a very effective defoamer for water based emulsion paints and coatings. Through the good emulsifiability of **SCHWEGO[®] eco foam 6326** is the incorporation in the paint system easier compared with typical mineral oil defoamer.

Applications: **SCHWEGO[®] eco foam 6326** can be used in emulsion paints based on styrene / acrylate, pure acrylate or vinylacetate dispersions from high till low PVC, silicate paints, adhesives, plasters, waterbased industrial coatings and to prevent foam at the polymerization of dispersions.

Technical data:
(Guide values)

Appearance	:	white liquid
Density (ISO 2811-1)	:	0,95 g/cm ³
Active matter	:	100 %

Processing: **SCHWEGO[®] eco foam 6326** can be used in all steps of the paint production. To achieve the optimum of the efficiency is the best to incorporate **SCHWEGO[®] eco foam 6326** with 50% in the mill base and with 50 % in the let down. The dosage is between 0.2 - 0.7 %, calculated on total system.

Storage: Do not store **SCHWEGO[®] eco foam 6326** lower than 5°C. Stir it up before use. Keep it in a cool, well-ventilated place. Protect **SCHWEGO[®] eco foam 6326** for frost. Subject to appropriate storage, the described properties of **SCHWEGO[®] eco foam 6326** remain stable for at least 12 months, provided the original container is closed after use.

Packaging: 25 kg / 50 kg / 180 kg drum, 850 kg container

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary.
Further safety instructions please learn from our material safety data sheet. 12/2022