

SCHWEGO[®] foam 6331

Deaerating additive for solvent borne, water-based and solvent free coating systems, free of silicone

Composition: Polymer in solvent

Properties: **SCHWEGO[®] foam 6331** prevent macro – and micro foam. **SCHWEGO[®] foam 6331** improve the levelling, prevents cratering and cooker in stoving coatings in solvent borne, water-based and solvent free systems.

Applications: **SCHWEGO[®] foam 6331** is suitable for almost all solvent borne and water-based coating systems. It is particularly effective in printing inks.

Technical data:
(Guide values)

Appearance		: clear, colourless liquid
Density	(ISO 2811-1)	: 0.82 g/cm ³
Flash point	(ISO 1523)	: 8 °C
Active matter		: 100 %

Processing: The dosage of **SCHWEGO[®] foam 6331** is 0.5 – 2.0 % calculated on total system. **SCHWEGO[®] foam 6331** can be incorporated at any stage of the production.

Storage: Stir **SCHWEGO[®] foam 6331** up before use. Keep it in a cool, well-ventilated place. Subject to appropriate storage, the described properties of **SCHWEGO[®] foam 6331** remain stable for at least 12 months, provided the original container is closed after use.

Packaging: 50 kg / 175 kg drum

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary.

Further safety instructions please learn from our material safety data sheet. 03/2019