

SCHWEGO[®] foam 6360

Defoamer for water-based and UV-curing coatings, free of silicone

Chemical base: Polymer in solvent mixture

Properties: **SCHWEGO[®] foam 6360** is a product with interfacial activity which suppresses the formation of entrapped air in UV coatings, i.e. air bubbles are destroyed before the film dries. Cratering is prevented and levelling is promoted.

Applications: **SCHWEGO[®] foam 6360** shows excellent defoaming action in UV coatings and is also suitable for coatings based on alkyd, polyester, epoxy, PU and acrylate.

Technical data:
(Guide values)

Appearance		: clear, light yellowish liquid
Density	(ISO 2811-1)	: 0.96 g/cm ³
Flash point	(ISO 1523)	: > 100 °C
Active matter		: 100 %

Processing: **SCHWEGO[®] foam 6360** should be incorporated at the beginning of the production. Optimal is an addition before grinding of the pigments. Post addition is possible, provided **SCHWEGO[®] foam 6360** is homogeneously distributed. The dosage of **SCHWEGO[®] foam 6360** is 0.1 – 1.0 %, calculated on total formulation and is depending on system. Predilution with one of the solvents of the formulation is advisable.

Storage: Do not store **SCHWEGO[®] foam 6360** at temperatures below 0° C. Stir it up before use. Keep it in a cool, well-ventilated place. Subject to appropriate storage, the described properties of **SCHWEGO[®] foam 6360** remain stable for at least 2 years, provided the original container is closed after use.

Packaging: 50 kg / 175 kg drum

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary.
Further safety instructions please learn from our material safety data sheet. 03/2019