

SCHWEGO[®] eco foam 8338

Defoamer for water-based coating systems

Chemical base: Formulation of vegetable oils, contains small amount of silicone oil

Properties: **SCHWEGO[®] eco foam 8338** is a liquid, very effective defoaming additive and readily emulsifiable in water. He is in use as grinding- and coating defoamer.

Applications: **SCHWEGO[®] eco foam 8338** can be used in emulsion paints, water-based coatings, adhesives and plasters.

Technical data:
(Guide values)

Appearance	:	yellow, cloudy liquid
Density (ISO 2811-1)	:	0.98 g/cm ³
Flash point (ISO 1523)	:	> 100 °C
Active matter	:	100 %

Processing: **SCHWEGO[®] eco foam 8338** can be used at all steps in the paint production. If required it is possible to emulsify **SCHWEGO[®] eco foam 8338** in water before the incorporation. The dosage is dependent from the system. Normally it is between 0.2 – 0,5 %, calculated on total system. The dosage may be increased up to 1.0 %.

Storage: Do not store **SCHWEGO[®] eco foam 8338** at temperatures below 5 °C and above 30° C. Stir it up before use. Keep it in a cool, well-ventilated place. At temperatures below 0 °C the viscosity may rise. It is reversible by warming and stirring. There is no influence on product quality.

Subject to appropriate storage, the described properties of **SCHWEGO[®] eco foam 8338** remain stable for at least 12 months, provided the original container is closed after use.

Packaging: 50 kg / 175 kg drum

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary. Further safety instructions please learn from our material safety data sheet. 12/2022